


Ball joint steering mechanism and associated position sensor arrangement for motor vehicle use has a robust arrangement of permanent magnet signaler whose movement is detected by a sensor

Patent number: DE10110738
Publication date: 2002-11-07
Inventor: BUERGER FRIEDHELM (DE)
Applicant: BERGER BOEHRINGER & PARTNER GM (DE)
Classification:
- **international:** B60G7/00; B60G17/019; B62D7/16; B62D15/02; F16C11/06; B60G7/00; B60G17/015; B62D7/00; B62D15/00; F16C11/06; IPC1-7; F16C11/06; B60G7/02; B62D7/16; G01B7/30
- **europaen:** B62D15/02D4; B60G7/00B; B60G17/019; B62D7/16; F16C11/06C3C; F16C11/06C3F
Application number: DE20011010738 20010301
Priority number(s): DE20011010738 20010301

[Report a data error here](#)

Abstract of DE10110738

Ball joint has a ball joint housing that accepts a ball pin (20) so that it can be rotated and tilted. Within the joint is an integrated signaler-sensor (62, 72) arrangement that detects the position of the pin relative to the housing. The pin is sealed against external effects using a hardened bearing material. The signaler is a permanent magnet with its movement detected by a magnetically sensitive sensor. The magnet is arranged on a radius from the mid point (21) of the ball pin. Independent claims are made for a device for controlling the operating parameters of a motor vehicle based on the relative position of two steering elements, a steering gear, a track rod and a method for producing a ball joint with associated position determination arrangement all associated with a motor vehicle steering assembly.



Data supplied from the esp@cenet database - Worldwide